



Rack-mountable package available

UC-2000 Universal Laser Controller provides total control of your laser

easy control of power, duty cycle, and modulation frequency

Synrad's second generation laser controller, the UC-2000 provides an easy user interface for total control of laser power, duty cycle, and modulation frequency.

Power control is achieved by pulse width modulation (PWM) at selectable clock frequencies of 5, 10, and 20 kHz. Compatible with Synrad's entire line of CO₂ lasers, the all-digital UC-2000 features an easy-to-read LCD screen and easy setup. Available in standard or rack-mountable packages.

Features of the UC-2000 include:

- Real-time LCD display of operating mode and PWM power settings

- Control knob sets laser power in 0.5% or 5% increments
- Built-In Laser indicator
- Remote analog voltage or analog current power control
- DB9 serial connection allows UC-2000 control through an RS232 serial port from a computer or PLC
- Real-time display of power setpoint and actual closed loop power regulation
- Optional panel mount design available



UC-2000

Universal Laser Controller

Specifications

Power Input	15-50 VDC, 35 mA max.
PWM Output	100 mA, 50W CMOS driver
Gate Input	TTL or CMOS compatible, logic low 0-+0.9 VDC (laser off), logic high +2.8-+5.0 VDC (laser on)
Gate On Time, min	3.5 μ s
In closed loop mode	> 10 μ s
Clock Frequency	\pm 10% accuracy

Environmental Specifications

Operating Temperature	0°C-40°C
Humidity	0-80%, non-condensing



Dimensions

Length	7.00 in (177.9 mm)
Width	4.23 in (107.4 mm)
Height	2.10 in (53.3 mm)
Weight	1.14 lbs (0.52 kg)

Operating Modes

	Input	Output
Standby	none	1 μ s, 5 kHz Tickle signal
Manual	PWM Adj Knob	1 μ s, 5 kHz Tickle signal, 0-95% (or 99%) PWM duty cycle at 5, 10, or 20 kHz
Analog Current (ANC)	4-20 mA current, \pm 5%, 100mA max, Input resistance=220 Ω to ground	1 μ s, 5kHz Tickle signal @ 4mA, to 99% PWM duty cycle signal at 5, 10, or 20 kHz @ 20 mA
Analog Voltage (ANV)	0-10 VDC, \pm 5%, +15VDC max, Input resistance=10k Ω to ground	1 μ s, 5kHz Tickle signal @ 0 V (<100 mV), to 99% PWM duty cycle signal at 5, 10 or 20 kHz @ 10 VDC
Manual Closed Loop Control*	PWM Adj Knob	1 μ s, 5KHz Tickle signal, 0-99% PWM duty cycle at 5, 10 or 20 kHz
ANV Closed Loop Control*	0-10 VDC, \pm 5%, +15VDC max, Input resistance=10k Ω to ground	1 μ s, 5kHz Tickle signal @ 0 V (<100 mV), to 99% PWM duty cycle at 5, 10 or 20 kHz @10 VDC
Remote	Software commands via RS232 serial port protocols	Manual, ANC, ANV, Man. Closed Loop, or ANV Closed Loop mode signal

* Available only for Synrad's 48-1 (10W) and 48-2 (25W) lasers with a factory installed 48-CL Closed Loop Stabilization Kit



dimensions are in inches (millimeters)

1.800.SYNRAD1



An Excel Technology Company